

Grade 70 Transport Chain

Grade 70 Transport chain is considered the chain of choice for load binding applications. It is also well suited for tiedowns/ lashings and logging applications.

Secure a load grade 70 chain complies to AS/NZ4344-2001. Every batch is independently tested and test certificates are available upon request.

Grade 70 transport chain is electroplated gold to resist oxidization and is sold either by the metre or drum lot.

Grade 70 Chain must NEVER be used for LIFTING.



Chain Marking	Chain Size	Lashing Capacity	Weight per metre
4344 - 2.3	6 mm	2300 kg	1.25 kg
4344 - 4.0	8 mm	4000 kg	1.43 kg
4344 - 6.0	10 mm	6000 kg	2.23 kg
4344 - 9.0	13 mm	9000 kg	3.37 kg

Load Binders with Winged Grab Hooks

We supply the standard lever type, ratchet type and recoilless type. These are made to comply with AS/NZ4344 - 2001. Loadbinders are forged and tempered with Winged Grab Hooks which allows for maximum lashing capacity. Winged grab hooks have cradles on both sides of the outer jaws, thus preventing any deformation to the chain during tensioning and allows full 100% lashing capacity of the chain.

Lever Type - Ratchet Type - Recoiless

Chain Size	Lashing Capacity
6 mm	2300 kg
8 mm	4000 kg
10 mm	6000 kg
13 mm	9000 kg



Combo Buckets

9 metres of 6mm - 8mm - 10mm - 13mm Grade 70 Chain with winged grab hooks each end. Supplied in a convenient plastic bucket with a handle for easy storage and handling.

