

Flat Slings

Secure A Load flat webbing slings are made of high tensile polyester yarn treated and coated for increased working life. These slings are used extensively for many different types of cargo handling in all types of conditions. They will not damage polished or fragile surfaces and will exert less pressure than wire ropes or chain at the point of contact with the load.

Colour coded according to DIN-EN 1492-1	Working Load Limits with 1 webbing sling					Working Load Limits with 1 webbing sling			
	Straight lift	Choked lift	0-7	7-45	45-60	Straight lift up to 45	Choked lift up to 45	Straight lift 45-60	Straight lift 45-60
	1,0	0,8	2,0	1,4	1,0	1,4	1,12	1,0	0,8
WILL 1†	1000	800	2000	1400	1000	1400	1120	1000	800
WILL 2†	2000	1600	4000	2800	2000	2800	2240	2000	1600
WILL 3†	3000	2400	6000	4200	3000	4200	3360	3000	2400
WILL 4†	4000	3200	8000	5600	4000	5600	4480	4000	3200

All Slings manufactured to AS 1353.1-1997. These slings are colour coded with 8:1 safety factor.

Round Slings

Round slings are easy to use, efficient in operation and gentle on surface contact. All round slings are colour coded to give easy identification of the safe working load. They come labelled, giving length and safe working load. The round sling inner core is made from high tensile polyester fibre, which is wound continuously without a join to provide the maximum possible strength. This core is protected by a tough woven tubular sleeve also made from polyester without side stitch. It serves to protect both the inner core of the sling and the surface of the product when lifting. The low stretch characteristics of the polyester yarn also prevents "LOAD BOUNCE" when lifting heavy loads. Round slings are unaffected by sunlight, humidity, grease and may be used in a multitude of lifting applications.

Colour coded according to DIN-EN 1492-1	Working Load Limits with 1 webbing sling							Working Load Limits with 1 webbing sling			
	Straight lift	Choked lift	0-7	Bis 7	7-45	45-60	45-60	Straight lift up to 45	Choked lift up to 45	Straight lift 45-60	Straight lift 45-60
	1,0	0,8	2,0	1,4	1,0	0,7	0,5	1,4	1,12	1,0	0,8
WILL 1†	1000	800	2000	1400	1000	700	500	1400	1120	1000	800
WILL 2†	2000	1600	4000	2800	2000	1400	1000	2800	2240	2000	1600
WILL 3†	3000	2400	6000	4200	3000	2100	1500	4200	3360	3000	2400
WILL 4†	4000	3200	8000	5600	4000	2800	2000	5600	4480	4000	3200
WILL 5†	5000	4000	10000	7000	5000	3500	2500	7000	5600	5000	4000
WILL 6†	6000	4800	12000	8400	6000	4200	3000	8400	6720	6000	4800
WILL 8†	8000	6400	16000	11200	8000	5600	4000	11200	8960	8000	6400
WILL 10†	10000	8000	20000	14000	10000	7000	5000	14000	11200	10000	8000
WILL 12†	12000	9600	24000	16800	12000	8400	6000	16800	13440	12000	9600

All Slings manufactured to AS 4497.1-1997. These slings are colour coded with 7:1 safety factor.